

PETROL GENERATORS

Robust & reliable solutions for providing power

THE MOST COMPACT GENERATORS on the market with 15% more power. They can deliver 3 phase and single phase power at the same time. With less than 3% total harmonic distortion they are ideal for high-frequency applications.

CHALLENGE ON THE JOB?

- Having power near to where I am working
- Combining 3 phase and single phase outlets
- Being easy to move on and off vehicles
- Tight access

SOLUTIONS

- ✓ Most compact portable generator on market
- ✓ 15% more power from the same engines
- ✓ 3 phase & single phase paralleling capacity
- ✓ Easy to position near working area
- ✓ 3 year warranty

AVAILABLE MODELS

GEN-10P SPECIFICATIONS

Max output	10kVA/8kW
Frequency	50Hz
Voltage	240V/415V
Rated output	6400W
Sockets	Sockets 2 x 15A single phase + 1 x 20A 3 phase sockets with RCBO protection
DRY Weight	100kg
Noise level (7m)	No load - 72dB 50% load - 76dB 100% load - 78dB
Engine	Honda GX-390
Starting system	Pull start
Fuel economy	2.3 L/h @ 50% load
Dimensions	598mm (23in) [L] x 609mm (24in) [W] x 1162mm (46in) [H]



GEN-23P SPECIFICATIONS

Max output	23kVA/19kW
Frequency	50Hz
Voltage	240/415V
Rated output	18,000W
Sockets	2x15A Single Phase and/or 32A 3-phase sockets with RCBO protection
DRY Weight	240kgs
Noise level (7m)	50% Load - 78dB
Engine	Vanguard EFI 37hp
Starting system	Electric/Key Start
Fuel economy	5.6 L/h @ 50% load
Dimensions	1105mm (43.5in) [L] x 632mm (24.8in) [W] x 1024mm (40.3in) [H]



GEN-16P SPECIFICATIONS

Max output	16kVA/19kW
Frequency	50Hz
Voltage	240/415V
Rated output	12,500W
Sockets	2x15A Single Phase and/or 32A 3-phase sockets with RCBO protection
DRY Weight	155kgs
Noise level (7m)	No Load - 72dB 50% Load - 76dB 100% Load - 78dB
Engine	GX-690
Starting system	Electric/Key Start
Fuel economy	4.9 L/h @ 50% load
Dimensions	773mm (30in) [L] x 530mm (21in) [W] x 902mm (36in) [H]



GEN-32P SPECIFICATIONS

Max output	30kVA/28kW
Frequency	50Hz
Voltage	240/415V
Rated output	25000W
Sockets	2x15A Single Phase + 2x32A 3-phase sockets with RCBO protection
DRY Weight	320kgs
Noise level (7m)	50% Load - 72-76dB
Engine	Honda GX-690 x 2
Starting system	Electric/Key Start
Fuel economy	9.8 L/h @ 50% load
Dimensions	1105mm (43.5in) [L] x 632mm (24.8in) [W] x 1206mm (47.4in) [H]



Extremely manouverable. We ran a 3 phase grinder, a single phase grinder and a vacuum all at the same time.

Jason, Concrete Artisans



GEN-23P 23Kva



ACCESSORIES

1



1. Rubber feet

2



2. Rubber Handle grips

3



3. Generator Adapter Plug
20A - 32A

4



4. Machine Adapter Plug
with breaker 32A - 20A

Please refer to page 25 for part numbers

PARALLEL BOX

GEN-16P &
GEN-10P
WITH
PARALLEL
BOX



>> Visit our website to see the Generators in use

1300 795 953 · makinex.com.au