## Sika® Primer-3 N



Version Date of last issue: -Revision Date: SDS Number:

000000120488 Date of first issue: 08.07.2021 08.07.2021 1.0

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Sika® Primer-3 N

Product code : 000000120488

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park. NSW 2164

Telephone : +61 2 9725 11 45 Telefax +61 2 9725 33 30 Emergency telephone num-: +61 1800 033 111

Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent, Primer

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids : Category 2

Serious eye damage/eye irri-

tation

Category 2A

single exposure

Specific target organ toxicity - : Category 3 (Central nervous system)

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

**GHS** label elements

Hazard pictograms





Signal word

Hazard statements H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements Prevention:

## Sika® Primer-3 N



Version Revision Date: SDS Number: Date of last issue: -

1.0 08.07.2021 000000120488 Date of first issue: 08.07.2021

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist or vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

#### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards which do not result in classification

None known.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

## Components

Chemical name	CAS-No.	Concentration (% w/w)
ethyl acetate	141-78-6	>= 30 -< 60
xylene	1330-20-7	< 10
propan-2-ol	67-63-0	< 10
ethylbenzene	100-41-4	< 10
methanol	67-56-1	< 1

## Sika® Primer-3 N



Version Revision Date: SDS Number: Date of last issue: -

1.0 08.07.2021 000000120488 Date of first issue: 08.07.2021

dibutyltin dilaurate 77-58-7 < 0.3

**SECTION 4. FIRST AID MEASURES** 

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

delayed

irritant effects

**Excessive lachrymation** 

Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Causes serious eye irritation. May cause drowsiness or dizziness.

Notes to physician : Treat symptomatically.

**SECTION 5. FIREFIGHTING MEASURES** 

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Water

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ode

Use water spray to cool unopened containers.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

## Sika® Primer-3 N



Version Revision Date: SDS Number: Date of last issue: -

1.0 08.07.2021 000000120488 Date of first issue: 08.07.2021

for firefighters

Hazchem Code : •3YE

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

Use explosion-proof equipment.

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Take precautionary measures against electrostatic discharg-

es.

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Store in cool place.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

# Sika® Primer-3 N



Version Revision Date: SDS Number: Date of last issue: -

1.0 08.07.2021 000000120488 Date of first issue: 08.07.2021

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
ethyl acetate	141-78-6	STEL	400 ppm 1,440 mg/m3	AU OEL	
		TWA	200 ppm 720 mg/m3	AU OEL	
xylene	1330-20-7	STEL	150 ppm 655 mg/m3	AU OEL	
		TWA	80 ppm 350 mg/m3	AU OEL	
propan-2-ol	67-63-0	TWA	400 ppm 983 mg/m3	AU OEL	
		STEL	500 ppm 1,230 mg/m3	AU OEL	
ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m3	AU OEL	
		STEL	125 ppm 543 mg/m3	AU OEL	
methanol	67-56-1	TWA	200 ppm 262 mg/m3	AU OEL	
	Further inform	Further information: Skin absorption			
		STEL	250 ppm 328 mg/m3	AU OEL	

# **Biological occupational exposure limits**

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
xylene	1330-20-7	Methylhip- puric acids	Urine	End of shift (As	1.5 g/g creat- inine	ACGIH BEI
				soon as possible		
				after ex-		
				posure		
				ceases)		
propan-2-ol	67-63-0	Acetone	Urine	End of	40 mg/l	ACGIH
				shift at		BEI
				end of		
				workweek		
ethylbenzene	100-41-4	Sum of	Urine	End of	0.15 g/g cre-	ACGIH
		mandelic		shift (As	atinine	BEI
		acid and		soon as		
		phenyl gly-		possible		

# Sika® Primer-3 N



Version Revision Date: SDS Number: Date of last issue: -

1.0 08.07.2021 000000120488 Date of first issue: 08.07.2021

		oxylic acid		after ex- posure ceases)		
methanol	67-56-1	Methanol	Urine	End of shift (As	15 mg/l	ACGIH BEI
				soon as possible		
				after ex-		
				posure		
				ceases)		

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Avoid vapor formation.

Provide appropriate exhaust ventilation at places where va-

por is formed.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

organic vapor filter (Type A)

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

Protective clothing needs to be made of cotton.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES** 

Appearance : liquid

Colour : colourless

Odour : very faint

Odour Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/range / Freezing :

point

No data available

## Sika® Primer-3 N



Version Revision Date: SDS Number: Date of last issue: -

1.0 08.07.2021 000000120488 Date of first issue: 08.07.2021

Boiling point/boiling range : No data available

Flash point : ca. -4 °C (25 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

7 %(V)

Lower explosion limit / Lower

flammability limit

1 %(V)

Vapour pressure : 99.9915 hPa

Relative vapour density : No data available

Density : ca. 0.98 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : 425 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 10 mPa.s (20 °C (68 °F))

Viscosity, kinematic : < 20.5 mm2/s ( 40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 66.6% w/w

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- : Stable under recommended storage conditions.

## Sika® Primer-3 N



Version Revision Date: SDS Number: Date of last issue: -

1.0 08.07.2021 000000120488 Date of first issue: 08.07.2021

tions Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : see section 7.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Acute toxicity**

Not classified based on available information.

Components:

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): ca. 1,600 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,700 mg/kg

propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): < 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

methanol:

Acute inhalation toxicity : LC50: 3 mg/l

Exposure time: 4 h Test atmosphere: vapour

Method: Converted acute toxicity point estimate

dibutyltin dilaurate:

Acute oral toxicity : LD50 Oral (Rat): 2,071 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

## Sika® Primer-3 N



Version Date of last issue: -Revision Date: SDS Number:

08.07.2021 000000120488 Date of first issue: 08.07.2021 1.0

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

### Skin sensitisation

Not classified based on available information.

## **Respiratory sensitisation**

Not classified based on available information.

### **Chronic toxicity**

### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

May cause drowsiness or dizziness.

## STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

### **Components:**

xylene:

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 2.2

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l

Exposure time: 56 d

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia (water flea)): 1.17 mg/l

Exposure time: 7 d

propan-2-ol:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

# Sika® Primer-3 N



Version Date of last issue: -Revision Date: SDS Number:

08.07.2021 000000120488 Date of first issue: 08.07.2021 1.0

aquatic invertebrates

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 9,714 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Scenedesmus capricornutum (fresh water algae)): >

100 mg/l

Exposure time: 72 h

ethylbenzene:

M-Factor (Acute aquatic tox- : 1

icity)

dibutyltin dilaurate:

Toxicity to fish LC50 (Fish): 3.1 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 1 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50 (Selenastrum capricornutum (green algae)): 1 - 10 mg/l

Exposure time: 72 h

M-Factor (Acute aquatic tox- :

icity)

M-Factor (Chronic aquatic

toxicity)

### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

### Mobility in soil

No data available

#### Other adverse effects

**Product:** 

Additional ecological infor-

mation

: Harmful to aquatic life with long lasting effects.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

## Sika® Primer-3 N



Version Revision Date: SDS Number: Date of last issue: -

1.0 08.07.2021 000000120488 Date of first issue: 08.07.2021

Do not burn, or use a cutting torch on, the empty drum.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

#### **SECTION 14. TRANSPORT INFORMATION**

## **International Regulations**

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo : 364

aircraft)

Packing instruction (passen- : 353

ger aircraft)

**IMDG-Code** 

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3

EmS Code : F-E, S-E Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **National Regulations**

**ADG** 

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3
Hazchem Code : •3YE

## Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated

Scheduling of Medicines and

# Sika® Primer-3 N



Version Revision Date: SDS Number: Date of last issue: -

1.0 08.07.2021 000000120488 Date of first issue: 08.07.2021

**Poisons** 

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

**SECTION 16. OTHER INFORMATION** 

Revision Date : 08.07.2021 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

# Sika® Primer-3 N



Version Revision Date: SDS Number: Date of last issue: -

1.0 08.07.2021 000000120488 Date of first issue: 08.07.2021

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN